## 2021

## Can-am. OUTLANDER XT 650 /1000R

## **HIGHLIGHTS**

- Rotax® V-Twin engine options
- · Arched double A-arm front suspension with front sway bar
- · Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,500 lb (1,588 kg) winch
- · Heavy-duty front and rear bumpers
- · Handlebar wind deflectors
- Painted plastics for premium look
- 14 in. cast-aluminum wheels
- 26 in. ITP† Terracross† radial tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing-Arm Independent (TTI) rear suspension
- 625 W magneto
- High-strength, multifunction racks with LinQ<sup>™</sup> quick-attach accessory system
- 5.7 gal (21.4 L) water-resistant rear compartment
- RF DESS key

ENIQUALEC

Rear



Boreal Green / 650 / 1000R

**DIMENSIONS &** 

Seat

650	1000R
62 hp, Rotax 649.6 cc V-twin, liquid cooled	91 hp, Rotax 976 cc V-twin, Iiquid cooled
Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
CVT, P/R/N/H/L, standard engine braking	
Selectable 2WD/4WD with Visco-Lok¹ QE auto-locking front differential	
Tri-Mode Dynamic Power Steering (DPS)	
Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel	
C	Dil
Torsional Trailing-Arm Independent (TTI) 9.9 in. (25.1 cm) travel	
C	Dil
ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)	
ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)	
14 in. cast-aluminum	
Dual 214 mm ventilated disc brakes	
	62 hp, Rotax 649.6 cc V-twin, liquid cooled  Electronic Fuel Injection (EFI)  CVT, P/R/N/H/L, sta Selectable with Visco-Lok† QE auto Tri-Mode Dynamic F  Arched double A-arr 9.2 in. (23.3)  CO Torsional Trailing-Ar 9.9 in. (25.1)  ITP Terracross 26 x 8 x 1.1  ITP Terracross 26 x 10 x 1  14 in. cast

with hydraulic twin-piston calipers
Single 214 mm ventilated disc brake

with hydraulic twin-piston caliper

CAPACITIES	650	1000R
Estimated Dry Weight*	749 lb (341kg)	826 lb (375 kg)
LxWxH	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	11 in.	(27.9 cm)
Seat Height	34.5 in	. (87.7 cm)
Rack Capacity	Front: 100 lb (45 kg	g)/Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	
FEATURES		
Gauge	4.5 in. digital display: Speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock	
Instrumentation		Coutlet in console, tor in the back (15 A)
Anti-theft System	RF Digitally Encoded S	ecurity System (D.E.S.S.™)
Lighting		in 60 W projectors rs with tail light/brake light
Winch	3,500 lb (1,	588 kg) winch

Protection	Heavy-duty front and rear bumpers Handlebar wind deflectors Mudguards
WARRANTY	
Factory Warranty	2 years BRP limited warranty

Standard

